

MULTICOM 2000®

Administrative Communications System

Operating Instructions

Compliance

Warning: Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his or her own expense.

This digital apparatus does not exceed the Class A limits for radio noise emissions from digital apparatus set out in the Radio Interference Regulations of the Canadian Department of Communications.

Le present appareil numerique n'emet pas de bruits radioelectriques depassant les limites applicables aux appareils numeriques del la class A prescrites dans le Reglement sur le brouillage radioelectrique edicte par le ministere des Communications du Canada.

Software Release

The information supplied in these instructions is applicable to systems with at least the following software revision levels:

System Software Level — 4.3 Administrative Telephone Software Level — 4.0

Bogen Communications, Inc. makes no representation or warranties with respect to these instructions. Bogen Communications, Inc. reserves the right to make changes in the specifications of the product described in these instructions without notice and without obligation of Bogen Communications, Inc. to notify any person of such revision or change.

Table of Contents

Introduction	4
Telephonic Features	4
Sound System Features	4
Additional Features Available	4
Station Types and Access Levels	5
Staff Station	5
Enhanced Staff Station	5
Administrative Station	6
Outside Line Stations	7
Operation of Staff Stations	8
Loudspeaker with Call Switch	8
Loudspeaker with Telephone Handset	8
Operation of Enhanced Staff Stations	9
System Functions for Enhanced Staff Stations	
Operation of Administrative Stations	10
Queue Operation for Incoming Calls	10
Using Auto-Dial and Scroll to Return Calls	11
Clearing the Call-Waiting Queue	11
Single-Zone and All Station Paging	12
Using the Main Menu System	12
1 - Emergency	12
2 - Audio Program	13
3 - Media Assign	14
4 - External	
5 - Setup	
6 - Manual Tone	
7 - Call Forward	
8 - Outside Line	
9 - Media Control	
System Functions for Administrative Stations	
Other Sequences	18
Summary of Main Menu System	10

Introduction

Bogen's Multicom 2000 is a microprocessor-based communications systems. The system combines the features of an electronic telephone network with the capabilities of a sound and program distribution system. Optional functions further increase the versatility of the system.

Telephonic Features:

- Two-way communication between stations.
- Normal/Urgent/Emergency calling from staff stations.
- Call transfer/call forward/call conference capabilities.
- · Remote answer.
- DTMF push-button dialing telephones. Standard dial and busy tones. Special ring signals on administrative phones annunciate emergency, urgent and normal, outside line calls, and calls waiting.

Sound System Features:

- Emergency All-Call and Emergency alarms capture complete system priority. Four alarm tones are available.
- Built-in audio program interface. Choose from three program sources and distribute program to any speaker, zones
 or all speakers.
- 8 Paging zones. Single zone paging.
- 8 Time signaling zones.
- 8 separate time signalling schedules.
- 1024 programmable events.
- Manual tone activation. 8 tones available plus external audio.

Additional Features Available:

- Integration with Bogen Multi-Graphic equipment.
- · Emergency announce link.
- Selective outside line access and ability to receive outside calls.
- Direct Inward Station Access (DISA) permits control of system functions from off-site telephone.
- Media control function.
- Relay control function to activate external equipment.
- Program clock control.
- Computer interface for remote diagnostics/programming.
- 4-digit dialing (requires MCDS3 phone)

Note: The Emergency Announce Link requires a loudspeaker at the calling location and at the emergency announce station.

Station Types and Access Levels

Each station port in the Multicom 2000 system is assigned an access level. The access level determines the type of equipment that can be connected to the port, as well as the ability to control different system functions.

Staff Station

A staff station consists of a loudspeaker and call switch, or a loudspeaker and telephone handset. Staff stations can receive calls from enhanced staff, administrative and outside line stations. Each staff station is programmed to ring one administrative station during "day" hours and one administrative station during "night" hours. The station's access level determines its call-in ability as follows:

- Level 1 Can make a normal or emergency call.
- Level 2 Can make an urgent or emergency call.
- Level 3 Can make an emergency call.

Enhanced Staff Station

An enhanced staff station consists of a DTMF dialing telephone and loudspeaker. System functions are initiated by pressing designated keys of the telephone dial pad. The access level of the station determines the ability to initiate system functions as follows:

Level 4

- Dial an administrative station.
- Make an emergency call to a designated administrative station (requires loudspeaker at calling location).
- Turn program material on/off at that location.
- · Remote answer.
- Ring for incoming outside line calls. (If the station is in use, an outside line calling in results in a call-waiting tone over the handset of the called party. The outside line will ring in when the station hangs up.)
- Access outside line (must be programmed).
- Call forward (Enhanced to Enhanced or Enhanced to Administrative).

Level 5 – Level 4 capabilities, plus:

- Call any staff or enhanced staff station.
- Conference call. (The third party in a conference call or call transfer can be any staff, enhanced staff, administrative or DISA station programmed for outgoing calls.)
- Transfer call.

Level 6 – Level 5 capabilities, plus:

- All-station page (all-call).
- Single zone page.

Administrative Station

An administrative station consists of a Model MCDS3 administrative telephone and optional loudspeaker. The administrative telephone is equipped with an alphanumeric display panel. The display panel normally shows the numbers and calling status of the first four stations calling in to that particular station (the display can be scrolled to show the numbers of other calling stations). The display also shows the time, day of the week, the current time-signalling schedule and the call-forward status (if active).

System functions are initiated by pressing designated keys of the telephone dial pad. Operation of system functions is assisted by the use of menus which appear on the display panel. The access level of the station determines the ability to initiate system functions as follows:

Level 7

- Dial any station.
- Turn program material on/off at that location.
- Scroll/Clear/Auto-Dial call-waiting queue.
- Conference call.
- Transfer call.
- Call forward (Administrative to Administrative only).
- Assign media functions (optional).
- All-station page (all-call).
- Emergency all-call page.
- Remote answer.
- Ring for incoming outside line calls. (If the station is in use, an outside line calling in results in a call-waiting tone over the handset of the called party. The outside line will ring in when the station hangs up.)
- Access outside line (must be programmed).

Level 8 – Level 7 capabilities, plus:

- Select program source.
- Distribute/cancel program.
- Activate alarm signals.
- Activate/reset external relay drivers.
- Single zone page.

Level 9 - Level 8 capabilities, plus:

- Manually activate tone signals.
- Bump/join conversation in progress.
- Access the system's Setup and Initialization menu systems and change system parameters.

Outside Line Stations

An optional feature of the Multicom 2000 system permits connection to outside telephone lines. This feature uses an optional circuit card which provides up to eight outside line station ports. Up to 2 telco cards can be installed in a system for a maximum of 15 outside lines on a fully expanded system.

The ability to access the outside lines for the purpose of placing outside calls can be assigned to any enhanced staff or administrative station in the system. This ability can be restricted to making local calls only or unrestricted, permitting local or long-distance calls.

There are two programmable levels for outside line stations:

Level 10 – The station port will ring a designated "day" or "night" staff, enhanced staff or administrative telephone for outside line calls. Administrative telephones annunciate outside line calls with a special ringing tone.

Level 11 – The station port will provide Multicom 2000 system dial tone when accessed from an outside telephone (DISA). This feature can be restricted by a password.

- If a password is required, functions available are: Call a station loudspeaker (no preannounce/privacy tone) or station telephone; make all-station & single zone page (no preannounce/privacy tone); access the Setup menu.
- If a password is not required, functions available are: Call a station loudspeaker (preannounce/privacy tone) or station telephone; make all-station & single-zone page (preannounce/privacy tone); remote answer; access the Audio Program menu, Media Assign menu, External Driver menu, and Manual Tone menu.

Notes: When an outside line is requested, the system will check to see if the station has any private lines. If no private lines exist, or if none are available, the system will check to see if any outside lines are assigned to ring the calling station. If a line is found and not in use, it will be assigned to the calling station. If no line is found, the system will hunt all outside lines (Outside lines and DISA lines can be both incoming and outgoing or restricted to incoming calls).

Operation of Staff Stations

Loudspeaker with Call Switch

To make a normal call (or urgent call if the station is programmed for Level 2 access), press the call switch. You will hear a tone over the loudspeaker when the call is answered. Speak into the loudspeaker.

To make an emergency call, quickly press and release the call switch at least four times. You will hear a tone over the loud-speaker when the call is answered or when the call is transferred to the emergency announce link (if not answered in 15 seconds and the option is activated). Speak into the loudspeaker for help.

Loudspeaker with Telephone Handset

To make a normal call (or urgent call if the station is programmed for Level 2 access), lift the handset off the hook switch and replace it. You will hear a tone over the loudspeaker when the call is answered. If you want to have a private conversation, lift the handset. The conversation will automatically switch from loudspeaker to handset.

To make an emergency call, lift the handset off the hook switch and flash the switch at least four times. Replace the handset on the hook switch. You will hear a tone over the loudspeaker when the call is answered or when the call is transferred to the emergency announce link (if not answered in 15 seconds and the option is enabled). Speak into the loudspeaker for help.

Notes: If your station has been programmed as a Level 3 station, a single press of the call switch (or single flash of hook switch) will initiate an emergency call. You will hear a tone over the loudspeaker when the call is answered or when the call is transferred to the emergency announce link within 15 seconds (if this option is enabled). Speak into the loudspeaker for help.

In some installations, a station may have two (2) call switches or a handset and call switch (such as a dedicated emergency-call switch). Your training instructor will be able to instruct you as to the use of switches in these configurations.

Operation of Enhanced Staff Stations

To make a normal call to a loudspeaker, lift the handset and dial the three digit number of the desired station. Precede this number with the \times key if you want to call a station telephone instead of the loudspeaker. You will hear a preannounce tone when you are connected to the loudspeaker and a privacy beep every 16 sec. that you don't speak. If you call a telephone, you will hear the ringing tone.

To make an emergency call, lift the handset and flash the hook switch at least four times, then replace the handset (or press the dedicated emergency-call switch, if so equipped). You will hear a tone over the loudspeaker when the call is answered or when the call is transferred to the emergency announce link if not answered in 15 seconds (and this option is enabled). Speak into the loudspeaker for help.

System Functions for Enhanced Staff Stations

The chart below lists system functions available to enhanced staff stations, access levels, and dial sequences.

Function	Level	Dial Sequence
Alarm Distribution	4, 5, 6	# 9wxy XXXX 9wxy (1 oz) (1 oz) - 9wxy (1 oz) (5 jkl.)
Audio Program On/Off	4, 5, 6	(#) (Toggles)
Call Forward * : All Calls	4, 5, 6	(9wx) (7pas) (1az) plus Arch. No.
When Busy	4, 5, 6	(9WXY) (7PRS) (2ABC) plus Arch. No.
When No Answer	4, 5, 6	(9wx) (7prs) (3DEF) plus Arch. No.
When Busy or No Answer	4, 5, 6	(9wx) (7phs) (4GHI) plus Arch. No.
Cancel Call Forward	4, 5, 6	(9wxy) (7prs) (5ukl)
Conference/Transfer Call	5, 6	Flash Hook, Dial No. when second party answers, Flash Hook to Conference or Hang up to Transfer
Dial Administrative Station	4, 5, 6	nnn (Dial Speaker)
		# nnn (Dial Phone)
Dial Staff Station	5, 6	nnn (Dial Speaker)
		# nnn (Dial Phone)
Emergency All-Call	4, 5, 6	(#) (9wxr) xxxx (9wxr) (1 oz) (1 oz)
Place Outside Line Call * *	4, 5, 6	(Wait for Dial Tone)
Remote Answer	4, 5, 6	(7PRS) # nnn
Single-Zone/All Station Page	6	# (1 oz) = # (8 TUV) / # (0 OPER)

xxxx = 4-Digit System Password Backwards nnn = 3-Digit Architectural Number

^{*} Call forward to other enhanced staff or administrative stations. No call forward to/from emergency announce station.

^{* *} Outside Line Calls can be restricted to local calls only. Must be programmed for outside line access.

Operation of Administrative Stations

To call any station loudspeaker, lift the handset and dial the 3-digit architectural number of the desired station. Precede this number with the $\textcircled{\times}$ key if you want to call a station telephone instead of the loudspeaker. The number you are calling will appear on the top line of the display panel as you dial. You will hear a preannounce tone when you are connected to the loudspeaker and a privacy beep every 16 seconds that you don't speak. If you call a telephone, you will hear the ringing tone. To switch the use of the asterisk so that the preceding number called with an asterisk connects to the loudspeaker and the number alone rings the station, dial $\textcircled{\text{ (m)}} \textcircled{\text{ (#)}} \textcircled{\text{ (#)}} \textcircled{\text{ (#)}} \textcircled{\text{ (#)}} \textcircled{\text{ (#)}} \textcircled{\text{ (II)}}$. To restore the original functionality of the asterisk key, dial $\textcircled{\text{ (M)}} \textcircled{\text{ (#)}} \textcircled{\text{ (#)}} \textcircled{\text{ (M)}} \textcircled{\text{$

Queue Operation for Incoming Calls

Each administrative telephone is equipped with a display panel which normally shows the time, day of week and current time signalling schedule:



If a normal or urgent call from a staff station is placed, the architectural number of the calling station appears on the top line of the display and the phone rings for 45 seconds. If the call remains unanswered, the number remains on the top line for an additional 60 seconds (during which time, the call can be auto-dialed) and is then placed in the queue according to priority and time Urgent/Normal, older calls first (see illustration below).

If an emergency call from a staff or enhanced staff station is placed, the architectural number appears on the top line of the display along with the word HELP. The phone will sound a special ring signal and will continue to ring until the call is answered. If the emergency announce option is activated, the call will be routed to the emergency announce loudspeaker after 15 seconds, however, the administrative phone will continue to ring until the call is answered.

Emergency Call	110E	HELP	12:00
Urgent Call	120U		MON 2
Normal Call	100		2
Normal Call (Arrow indicates additional	105 V		
calls in the queue)			

An emergency call will interrupt a non-emergency call in progress at the designated administrative telephone.

Using Auto-Dial and Scroll to Return Calls

You can use the Auto-Dial function to call the station number appearing on the top line of the display panel.


Lift the handset and press \mathfrak{T} . The call-waiting queue shifts down one line and the word ADIAL appears on the top line. A small arrow points to the number on the second line and the call is placed.



ADIAL replaces station 120 U on the top line an arrow points to the station being Auto-Dialed.

You can scroll the queue to place any station number on the top line of the display, and then use the auto-dial function to return the call.

Lift the handset and press #. The display appears as shown below. Press # to scroll the queue. (Note: You will be prompted to WAIT for the action of each key press to be completed.) When the desired number appears on the top line of the display, press * twice. The word ADIAL and the arrow will appear as above and the call is placed.




Press # to Scroll queue

Press * to Clear queue (see below)

Clearing the Call-Waiting Queue

To clear all calls from the call-waiting queue, lift the handset and press #. The display shown below will appear. Press * to select the Clear Queue function. The display will then prompt you to press * to proceed or any other key to abort. If you proceed, the display will confirm the function and the queue (at that phone only) will be cleared.



Single-Zone and All-Station Paging

To make a single-zone or all-station page, lift the handset and press #. The display shown below will appear. Press the number keypad corresponding to the zone you want to page (1 through 8). To make an all-station page, press @ (the local speaker will be muted). Speak into the handset to make the page. Hang up the handset to end the page.

Zone ?	12:00
120U	MON 2
100	
105	

Enter number of the zone you want to page or 0 page all stations.

Hang up the handset to exit. this function.

Using the Main Menu System

- Main Menu -

1 - Emergency

2 - Audio Program

3 - Media

4 - External

5 - Setup

6 - Manual Tone

7 - Call Forward

8 - Outside Line

9 - Media Control

The Main Menu appears when you press 9vx.

To scroll the menu, press the .

To select a function, press the corresponding number key. The display will then prompt the user to enter additional information, confirm the initiation of the function, or provide a new menu to permit the selection of choices available for that function.

1 - Emergency

The Emergency menu lets you make an emergency all call or initiate one of four alarm tones. Hanging up the phone stops the page/alarm. Press (key to scroll the menu. Press to escape and return to the main menu.

- Emergency -

1 - All Call

2 - Alarm 1

3 - Alarm 2

4 - Alarm 3

5 - Alarm 4


0 - Escape

The Emergency menu lets you make an Emergency All-Call or sound one of four alarms.

Press (key to scroll the menu.

2 - Audio Program


The Audio Program menu controls the selection and distribution of program material. If a program source is connected, the administrative telephone's speaker will be connected regardless of whether or not program has been distributed. This allows monitoring of program source prior to distribution.



3 - Media

The Media Assign menu controls the assignment of remotely located video equipment to a station. The menu is used with the telemedia control option. The operator enters the architectural number of the media station number and the assigned architectural room number is returned (the cursor is positioned under room).

To enter a station assignment, with the cursor positioned under room, enter a valid station architectural number then press # to change the function of the * key to "Enter", and press *.



Note: Diagrams include menu selections not immediately displayed (those beneath the dashed line). Press the scroll buttons on the MCDS3 to view these selections. Press to escape.

Enter the media architectural station number and the architectural room number assigned is returned. To exit this menu, press # to change the function of the * key to "Exit", and then press *.


To review the media to room assignments, press # to change the function of the * key to "Review". Pressing * will then scroll through the current assignments (the cursor is positioned under room).

To delete any information displayed, press # to change the function of the \otimes key to "Delete". Pressing \otimes will then delete the currently displayed information.

4 - External

0 - Escape

The "External" menu lets you review, select or cancel external relay driver control circuits.



Note: Diagrams include menu selections not immediately displayed (those beneath the dashed line). Press the scroll buttons on the MCDS3 to view these selections. Press to escape.

To **Review** the status of the external relay drivers, press (102). A display will appear showing the current status of the four (4) external relays.

To **Select** an external relay driver, press (2480). Select the desired relay driver and press the appropriate key. The display will confirm the action. Press (0480) to escape.

To **Cancel** an external relay driver, press ③ Select the desired relay driver and press the appropriate key. To cancel all relay drivers, press ④. The display will confirm the action. Press ⑤ to escape.

To **Program** a relay driver, press 404. Enter relay number, on time and off time. To exit this menu, press # to change the function of the $\textcircled{\times}$ key to "Exit", and then press $\textcircled{\times}$.

To set **Twice-a-Day** closure, press (5m). You can set hour and number of seconds of closure (press (102)), and days of week (press (2m0)). Press (#) to exit.

To set **External Tone**, press 6 to exit.

To set Once-an-Hour closure, press (798). Enter minutes and duration. Press (#) to exit.

5 - Setup

The Setup menu is protected by a password and is available only from administrative stations assigned to Level 9.

The Setup menu permits setting the following parameters:

- Day/Time
- Time Signaling Events
- Time Zones
- Page Zones

The Setup menu also provides access to the Initialization/Diagnostic menu displays. These menus are protected by password and permit setting the following:

System Parameters

- Bell Duration
- Queue Time out
- Day Start Time
- Night Start Time
- Emergency Link
- Password
- Architectural Dialing On/Off
- Preannounce Tone On/Off
- Privacy Beep On/Off

Station Parameters

- Station Access Level
- Station Architectural Number
- "Day" Administrator
- "Night" Administrator
- Outside Line Access/DISA Password

Software Revision Level

Architectural/Station Number Cross Reference

4-Digit Dialing On/Off (requires MCDS3 phone)

Diagnostic Tests

- System Tests
- Card Tests

6 - Manual Tone

Selecting Manual Tone (No. 6 from Main Menu) displays the Initiate Tone menu and lets you initiate any of 8 tone signals over all system loudspeakers assigned to any of the 8 time zones. If no speakers have been assigned to any time zones, no tone will be heard.

- Initiate Tone 1 - Tone 1
2 - Tone 2
3 - Tone 3
4 - Tone 4
5 - Tone 5
6 - Tone 6
7 - Tone 7
8 - Tone 8
9 - Program 2
0 - Escape

The Initiate Tone menu lets you initiate any of 8 tone signals.

Press (P) (1) key to scroll the menu. Press (1) to escape to the Main menu.

Press the keypad corresponding to the tone number you want to initiate. The display will confirm the action. Press # to stop the tone and exit the display (or hang up).

7 - Call Forward

The Call Forward menu lets you forward calls to another administrative telephone. When call forwarding is activated a CF will appear on the lower right corner of the display. Upon entering the menu, an arrow will appear next to the active selection. No arrow appears if no selection is active.

- Call Forward 1 - All
2 - Busy
3 - No Answer
4 - Busy/No Ans.
5 - Cancel
0 - Escape

To forward all calls to another number, press $\textcircled{1}^{2}$. Enter the architectural number of the station you want to receive the call. Press # to enter. Press # to exit the menu.

To forward calls when your line is busy, press (2.ac). Enter the architectural number of the station you want to receive the call. Press (#) to enter. Press (#) to exit the menu.

To forward calls when there is no answer (15 seconds), press ③ Enter the architectural number of the station you want to receive the call. Press * to enter. Press # to exit the menu.

To forward calls when the line is busy or when there is no answer, press 400. Enter the architectural number of the station you want to receive the call. Press \times to enter. Press \oplus to exit the menu.

To cancel call forwarding, press 5 inc. The display will prompt you to press # to cancel or # to exit. If you press 1 in exit. If you press 1 to exit.

Note: The emergency link station cannot call forward to stations. No station can call forward to an emergency link station.

8 - Outside Line

The outside line menu will prompt you to wait until you hear dial tone before entering the number. The display will echo the number as you dial.

If you have a restricted line, you will be unable to dial more than 10 digits. For the first 30 seconds, the call cannot be transferred nor conferenced. Two outside lines may be joined in a conference call with any station programmed for outside line use. If the station phone hangs up, the outside lines are dropped.

- Outside Line -Wait For Dial Tone Then Dial #

The outside line menu prompts you to wait for dial tone before dialing the number.

9 - Media Control

Connection to a media station is via 1 of 2 ways. Assignment is made either through the media station architectural number directly. If a connection is made via the media station architectural number directly. If a connection is made via the media station architectural number to connect physically to the media station. A tone will be heard periodically as long as the assigned station is physically connected.

The station remains logically connected to the media controller even if the phone is hung up. No other station can connect to a media station that is logically connected to any other station. Once a station is logically connected, dialing (or the media station architectural number reconnects to the media station. No commands will be accepted by the media controller from the phone until a physical connection is established. The assigned station can logically disconnect from the media station by dialing (if the confirmation tone is not heard through the handset) and then dialing (or or or other delete key while the assignment is displayed. The Media Control menu operates the following media functions:

- Media Control -

1 - Play

2 - Pause

3 - Stop

4 - Rewind

5 - Fast Forword

6 - Channel Up

7 - TV/VCR

8 - Display

9 - Channel Down

0 - Power

- 2nd Function

* 0 - Disconnect

Note: Diagrams include menu selections not immediately displayed (those beneath the dashed line). Press the scroll buttons on the MCDS3 to view these selections. Press

Many more can be added but not displayed.

Do not leave the phone physically connected to the media station for long periods of time since this can prevent calls from being placed by other phones.

Note: If a station is already connected to one media station, a busy signal will be heard if an attempt is made to call another media station. If a media station is reserved, the station dialing the media station will hear a busy signal.

System Functions for Administrative Stations

The chart below lists available functions for administrative stations, the access level required, and the dial sequence required to access the specific function:

<u>Function</u>	<u>Level</u>	Dial Sequence
Alarm Distribution	8, 9	(9wxy) $(1oz)$ $(2abc)$ $=$ $(9wxy)$ $(1oz)$ $(5JKL)$
All-Call	7, 8, 9	# (0000)
Audio Program On/Off	7, 8, 9	* 9wx (Toggle)
Auto-Dial	7, 8, 9	(*)
Bump Conversation	9	Wait 10 seconds during busy
Call Forward All Calls	7, 8, 9	(9WXY) (7PRS) (102) plus Arch. No.
Call Fwd When Busy	7, 8, 9	(9WXY) (7PRS) (2ABC) plus Arch. No.
Call Fwd When No Answer	7, 8, 9	(9WXY) (7PRS) (3OEF) plus Arch. No.
Call Fwd When Busy or No Answer	7, 8, 9	(9WXY) (7PRS) (4GH) plus Arch. No.
Cancel Call Forward	7, 8, 9	(9WXY) (7PRS) (5JKL)
Conference/Transfer Call	7, 8, 9	Flash hook, Dial No., Flash hook
		When second party answers, flash hook
		to conference or hang up to transfer.
Dial Administrative Station	7, 8, 9	nnn (Dial Speaker), 迷 nnn (Dial Phone)
Dial Staff Station	7, 8, 9	nnn (Dial Speaker), 1∞ ★ nnn (Dial Phone)
Distribute/Cancel Program	8, 9	(9wxy) (2ABC) (2ABC)/(9wxy) (2ABC) (3DEF)
Emergency All Call	7, 8 ,9	(9wxy) (1 oz) (1 oz)
External Functions - Review/Select/Cancel	8, 9	(9wxy) (4GHI) (1 oz) = (9wxy) (4GHI) (30EF)
Join Conversation	9	* # nnn
Manually Initiate Tone	9	(9wxy) (6mno) (1 oz) = (9wxy) (6mno) (8tuv)
Media Assign	7, 8, 9	(9wxy) (3DEF)
Place Outside Line Call	7, 8, 9	(programmable)
Remote Answer	7, 8, 9	(7 _{PRS}) (★) nnn
Scroll/Erase Queue	7, 8, 9	# # / # *
Select Program Source	8, 9	$\begin{array}{cccccccccccccccccccccccccccccccccccc$
Special Functions Menu	9	(9wx) (5.vc.) pppp
Single Zone Page	8, 9	# (1 az) = # (8 ruv)

Notes: nnn = 3-Digit Architectural Number pppp = 4-Digit Password

Other Sequences

(102) * then hang up - sends a time update to the administrative telephone

 $(\mathbf{Z}^{ABC}) \times \mathbf{B}$ Baud rate change

TPRS ** nnn allows any ringing phone to be answered (nnn = architectural station no.)

An enhanced staff or administrative station can answer the first displayed station on the queue of another administrative station (after it ceases to ring) by dialing (PRS) (**) nnn, where nnn is the architectural number of the administrative telephone.

Summary of Main Menu System

9 1	Emergency Menu	9422	Select External #2
911	Emergency All Call	9423	Select External #3
912	Emergency Alarm #1	9424	Select External #4
913	Emergency Alarm #2	9420	Escape to External Menu
914	Emergency Alarm #3	9 4 3	Cancel Menu
9 1 5	Emergency Alarm #4	9431	Cancel External #1
910	Escape to Main Menu	9432	Cancel External #2
9 2	Audio Program Menu	9433	Cancel External #3
9 2 1	Select Program Menu	9434	Cancel External #4
9211	Select Program #1	943*	Cancel All External
9212	Select Program #2	9430	Escape to External Menu
9213	Select Program #3	9 5	Setup Menu - Password Required
9214	Cancel Current Program		to Proceed. See Installation & Setup Instructions
9210	Escape to Audio Program Menu	9 6	Initiate Tone Menu
922	Distribute Menu	961	Initiate Tone #1
9221	Select Speaker	962	Initiate Tone #2
9222	Select Zones	963	Initiate Tone #3
9223	Select All Speakers	964	Initiate Tone #4
9220	Escape to Audio Program Menu	965	Initiate Tone #5
923	Cancel Menu	966	Initiate Tone #6
9231	Cancel Speaker	967	Initiate Tone #7
9232	Cancel Zones	968	Initiate Tone #8
9233	Cancel All Speakers	969	External Audio Source
9230	Escape to Audio Program Menu	960	Escape to Main Menu
9 2 4	Review Program	9 7	Call Forward Menu
925	Query Program	971	Call Forward All Calls
920	Escape To Main Menu	972	Call Forward When Busy
9 3	Media Assign Menu	973	Call Forward When No Answer
9 3 1	Assign	974	Call Forward When Busy or
932	Television On/Off		No Answer
933	Television Schedule	975	Cancel Call Forward
9 3 0	Escape To Main Menu	970	Escape to Main Menu
9 4	External M enu	9 8	Outside Line
9 4 1	Review Menu	9 9	Media Control
9 4 2	Select Menu		
9 4 2 1	Select External #1		



50 Spring Street, Ramsey, NJ 07446, U.S.A. Tel. 201-934-8500; Fax: 201-934-9832; www.bogen.com